



Split Seasonal Range overview

Daikin's Split range has a solution for many applications. From the stylish to the discreet, Daikin's splits can be used to provide optimum comfort levels in homes and small commercial applications.



Engineered for Seasonal Efficiency, the range delivers top performance with Energy Labels upto A++, and are equipped with weekly timers and other features to generate further energy savings.

Ururu Sarara

A unique combination of humidification, dehumidification, ventilation and purification.



**Ururu
Sarara**

Emura and Nexura

A blend of iconic design and engineering excellence



DAIKIN
emura

A wall mounted unit designed for quiet and efficient operation.



nexura

Floor mounted unit with radiant heat front panel.

Split Indoor Units

The following indoor units can be paired with the RXS K/F outdoor unit. Details of capacities, Seasonal Efficiency Ratios and Energy Labels can be found in the table on the reverse.



FTXS-K



FTXS-G



FDXS-F



FVXS-F



FLXS-B



FCQG-F



FHQ-C




Split Pairings: Nominal versus Seasonal

| Fancoil | Capacity | Indoor | Outdoor | Nominal Efficiency | | Seasonal Efficiency - according to EN14825 | |
|--|----------|----------|-------------|--|--------------|--|--------------|
| | | | | EER / COP | Energy Label | SEER / SCOP | Energy Label |
| Ururu Sarara | 2.8kW | FTXR28E | RXR28E | 5.00 / 5.14 | A / A | 4.91 / 5.08 | B / A++ |
| | 4.2kW | FTXR42E | RXR42E | 4.00 / 4.32 | A / A | 5.46 / 4.50 | A / A+ |
| | 5.0kW | FTXR50E | RXR50E | 3.42 / 3.97 | A / A | 5.22 / 4.27 | A / A+ |
| Emura Wall Mount | 2.5kW | FTXG25J* | RXG25K | 4.46 / 4.36 | A / A | 6.53 / 4.34 | A++ / A+ |
| | 3.5kW | FTXG35J* | RXG35K | 3.93 / 4.04 | A / A | 6.51 / 4.23 | A++ / A+ |
| | 5.0kW | FTXG50J* | RXG50K | 3.21 / 3.63 | A / A | 5.45 / 3.87 | A++ / A+ |
| * JW = Emura in White, JA = Emura in brushed aluminium. Performance, labeling & SEER/SCOP are same for JA & JW | | | | | | | |
| Wall Mount | 2.0kW | FTXS20K | RXS20K | 4.65 / 4.55 | A / A | 5.71 / 4.75 | A+ / A++ |
| | 2.5kW | FTXS25K | RXS25K | 4.39 / 4.52 | A / A | 6.37 / 4.63 | A++ / A++ |
| | 3.5kW | FTXS35K | RXS35K | 4.27 / 4.82 | A / A | 6.89 / 5.03 | A++ / A++ |
| | 4.2kW | FTXS42K | RXS42K | 3.44 / 4.39 | A / A | 6.20 / 4.10 | A++ / A+ |
| | 5.0kW | FTXS50K | RXS50K | 3.47 / 4.53 | A / A | 6.35 / 4.45 | A++ / A+ |
| | 6.0kW | FTXS60K | RXS60F | 3.02 / 3.43 | B / B | 5.35 / 3.75 | A / A |
| | 7.1kW | FTXS71K | RXS71F | 3.02 / 3.22 | B / C | 5.23 / 3.59 | A / A |
| Wall Mount Low | 2.0kW | FTX20JV | RX20JV | 3.64 / 4.24 | A / A | 5.63 / 4.67 | A+ / A++ |
| | 2.5kW | FTX25JV | RX25JV | 3.42 / 4.06 | A / A | 5.63 / 4.50 | A+ / A+ |
| | 3.5kW | FTX35JV | RX35JV | 3.37 / 3.76 | A / A | 5.66 / 4.14 | A+ / A+ |
| | 5.0kW | FTX50GV | RX50GV | 3.23 / 3.63 | A / A | 5.63 / 4.08 | A+ / A+ |
| 6.0kW | FTX60GV | RX60GV | 3.02 / 3.43 | B / B | 5.10 / 3.74 | A / A | |
| Cooling Only RKS- J | | | | DOES NOT COMPLY WITH ErP DIRECTIVE & IS NO LONGER FOR SALE | | | |
| Nexura | 2.5kW | FVXG25K | RXG25K | 4.55 / 4.36 | A / A | 6.46 / 4.56 | A++ / A+ |
| | 3.5kW | FVXG35K | RXG35K | 3.68 / 3.72 | A / A | 6.33 / 3.93 | A++ / A |
| | 5.0kW | FVXG50K | RXG50K | 3.29 / 3.67 | A / A | 5.31 / 4.13 | A / A+ |
| Floor | 2.5kW | FVXS25F | RXS25K | 4.39 / 4.30 | A / A | 4.71 / 4.38 | B / A+ |
| | 3.5kW | FVXS35F | RXS35K | 3.43 / 3.69 | A / A | 4.93 / 3.83 | B / A |
| | 5.0kW | FVXS50F | RXS50K | 3.23 / 3.63 | A / A | 5.53 / 3.62 | A / A |
| Flexi | 2.5kW | FLXS25B | RXS25K | 3.85 / 3.47 | A / B | 4.46 / 3.63 | C / A |
| | 3.5kW | FLXS35B | RXS35K | 3.10 / 3.25 | A / A | 4.49 / 3.42 | C / A |
| | 5.0kW | FLXS50B | RXS50K | 2.85 / 3.35 | C / C | 5.09 / 3.68 | B / A |
| Ceiling | 3.5kW | FHQ35C | RXS35K | 3.58 / 3.96 | A / A | 4.89 / 3.98 | B / A |
| | 5.0kW | FHQ50C | RXS50K | 3.18 / 3.35 | B / C | 5.48 / 3.74 | A / A |
| | 6.0kW | FHQ60C | RXS60F | 3.26 / 3.32 | A / C | 5.54 / 3.50 | A / A |
| Cassette | 3.5kW | FCQG34F | RXS35K | 3.58 / 3.41 | A / B | 5.34 / 4.74 | A / A++ |
| | 5.0kW | FCQG50F | RXS50K | 3.55 / 3.70 | A / A | 5.89 / 4.25 | A+ / A+ |
| | 6.0kW | FCQG60F | RXS60F | 3.48 / 3.52 | A / B | 5.74 / 3.87 | A+ / A |
| 600 x 600 cassette | 2.5kW | FFQ25B9V | RXS25K | 3.43 / 3.48 | A / B | 4.36 / 3.75 | C / A |
| | 3.5kW | FFQ35B9V | RXS35K | 2.62 / 2.81 | D / D | 4.53 / 3.49 | C / A |
| | 5.0kW | FFQ50B9V | RXS50K | 2.62 / 2.81 | D / D | 5.14 / 3.41 | A / A |
| | 6.0kW | FFQ60B9V | RXS60F | 2.80 / 2.81 | F / F | 5.04 / 3.41 | B / A |
| Slim Ducted | 2.5kW | FDXS25F | RXS25K | 3.65 / 3.69 | A / A | 5.08 / 4.19 | B / A+ |
| | 3.5kW | FDXS35F | RXS35K | 3.28 / 3.56 | A / B | 4.82 / 3.81 | B / A |
| | 5.0kW | FDXS50F | RXS50K | 3.18 / 3.17 | B / D | 5.12 / 3.41 | A / A |
| | 6.0kW | FDXS60F | RXS60F | 2.96 / 3.17 | C / D | 5.50 / 3.51 | A / A |
| DC Ducted | 3.5kW | FBQ35C8 | RXS35K | 3.21 / 3.51 | A / B | 4.33 / 3.56 | C / A |
| | 5.0kW | FBQ50C8 | RXS50K | 3.03 / 3.42 | B / B | 4.96 / 3.53 | B / A |
| | 6.0kW | FBQ60C8 | RXS60F | 3.26 / 3.41 | B / A | 5.17 / 3.43 | A / A |


This table is for guidance only and should not be used for selection of equipment. Full equipment specification and details of Energy Label and Seasonal Data according to EN14825 can be found at www.daikin.co.uk

Nominal versus seasonal efficiency




Temperature

| NOMINAL | SEASONAL |
|---|--|
| 1 Temperature condition: 35°C for cooling 7°C for heating | Several rating temperatures for cooling and heating, reflecting actual performance over an entire season |
| Does not often occur in reality | |



Capacity

| NOMINAL | SEASONAL |
|---|--|
| Does not reflect partial capacity | Integrates operation at partial instead of full capacity |
| Benefits of inverter technology not visible | Benefits of inverter technology are shown |



AUX

Auxiliary modes

| NOMINAL | SEASONAL |
|--|--|
| Does not take auxiliary power modes into account | Includes consumption auxiliary modes: |
| | <ul style="list-style-type: none"> • Thermostat off • Standby mode • OFF mode • Crankcase heater |